


PITSOS PTI6E66G Chimney Hood, Black



SKU: IT65205

€299.00

Specifications

Technical Specifications

- 3 stages of normal operation and 1 intensive absorption: Intensive 1: Absorption rate 550 m³/h, noise level 65 (A) re1pW
- : Absorption rate 220 m³/h, noise level 46 (A) re1pW
- : Absorption rate 315 m³/h, noise level 53 (A) re1pW
- : Absorption rate 430 m³/h, noise level 60 (A) re1pW
- : According to EN 61591 and EN/IEC 60704-2-13
- 3 levels of normal operation and 1 of intensive air circulation: Intensive 1: Absorption rate 550 m³/h, noise level 72 (A) re1pW
- : Absorption rate 215 m³/h, noise level 51 (A) re1pW
- : Absorption rate 300 m³/h, noise level 61 (A) re1pW
- : Absorption rate 445 m³/h, noise level 69 (A) re1pW

- : According to EN 61591 and EN/IEC 60704-2-13
- Energy class: A
- Average annual energy consumption: 43.8 kWh
- Hydrodynamic efficiency: A
- Fat retention performance: E
- Total power: 223 W
- Number of bulbs: 2 x 3W
- Light intensity: 127 lux
- Color Temperature: 4000 K
- Lighting performance: A
- Automatic reset from intensive to normal setting after 5 minutes

General Specifications

- Type: Wall mounted
- Sloping design
- Black crystal surface
- Electronic control via Touch Control
- Capacity Motor
- Easy to clean smooth surfaces and materials
- Dishwasher-safe metal filters
- Large opening angle of the glass front with locking function for easy access to the filter and easy cleaning
- Tube diameter: Ø 15 cm
- Connection cable with plug: 1.5 m

Dimensions

- Extraction mode (HxWxD): 69-90 x 59 x 32.5 cm
- Recycling mode (HxWxD): 72-97.5 x 59 x 32.5 cm